



Value delivered. Always

SIMPLIFYING MATERIAL HANDLING



TRANSPORTATION - STACKING - TOWING & HAULING - LOADING & LIFTING

TRANSPORTATION

HYDRAULIC PALLET TRUCKS



PV25

Standard Version

Fork length - 810/910/1150/1220mm Fork width - 520/685mm Light weight & highly maneuverable.



PV25 G /SS

Galvanised / Stainless Steel

For use in damp and corrosive environments. Ideal for chemical, paper, leather, food processing industries and cold storage.



PV20 EWS

Electronic Weighing Scale

Provided with an integrated weighing scale with printers as an option.



PV12 PRV

Paper Roll Version

Ideal for carrying cylindrical loads such as paper rolls and drums. Special forks fabricated to match cylindrical loads eliminating use of pallets.

ELECTRIC PALLET TRUCKS



SP20 / SP25

Ideal for high intensity movement over long distances. Increased manoeuvrability because of small turning radius. Offers high throughput in both factories & warehouses.



SP36 / SP50

Ideal for carrying heavy palletized load like castings, metal coils, engines. Best suited for heavy engineering industries.

SCISSOR HAND PALLET TRUCK



SHP10

SHP10B

Combines advantages of hand pallet truck and adjustable worktable. Available in both quick lift ϑ battery operated versions.

ELECTRIC PLATFORM TRUCK



EPT5 / 7.5

Ideal for transporting non standard, non palletized loads in stores and warehouses. Also used as an order picker.

STACKING

MANUAL STACKER



Suitable for in-plant operations where lifting is primary and transport distance is short.

ST15 WC (Wide Chassis)

SEMI-ELECTRIC STACKER



Powered with electric lift, essentially used where applications require intensive stacking.

ELECTRIC COUNTER BALANCE STACKER



SC18 / SC14


A perfect fork lift & stacker combination. Ideal for ONE VEHICLE DOES IT ALL operations.

1500kg

Lift height: up to 6300mm

ELECTRIC STACKERS

Versatile, useful in almost all industrial work environments. Its compact design and small turning radius makes it ideal for operation in narrow aisles and busy gangways. Essentially an in-plant equipment, it is used for intensive stacking and transportation in minimum cycle times.



ST12

ST15 SS FFTL

TOWING & HAULING

ELECTRIC TOW TRACTORS




CAPACITY 2000 to 5000kg

Ideal for towing within factories, warehouses and at airports. The new electric power steering coupled with small turning radius makes it ideal for operating in narrow aisles. Available in sit-on and stand-up versions.

TT20S / TT50S

LOADING & LIFTING



Ideal for loading / unloading applications at diverse industrial, retail and commercial establishments.

NEW LAUNCH

FREIGHT LIFT

2000kg



Lift height: up to 8000mm

WITHOUT ENCLOSURE

WITH ENCLOSURE

Ideal for vertical transportation of palletized and non-palletized goods in multi level warehouses and industries. Designed specifically for the purpose of moving freight and goods, these lifts are completely customizable and come with different variants of floor, wall surfaces and many other features.

FEATURES



Swing door with interlocking on carriage



Perforated sheet on all the 4 sides



Hose burst check valve for added safety



Pendant with emergency switch on all the floors



Limit switch cutoff on all the floors



Mechanical Interlock for Collapsible Gate

OPTIONAL FEATURES



Electromechanical Lock



Electromagnetic Lock

SAFETY FEATURES

- Swing door with interlocking on carriage
- Perforated sheet on all the 4 sides
- Hose burst check valve
- Pendant with emergency switch on all the floors
- Limit switch cut off on all the floors
- Emergency alarm
- Single phase protection
- Phase failure protection
- Reverse phase protection

- Interlocking collapsible gate on carriage
- SS 304 complete carriage
- Closed Carriage / Cabin Option
- Flame proof control panel & power pack
- · PLC control panel
- Beacon & beeper
- Enclosure interlocking type
- Mechanical lock Electromechanical Electromagnetic
- Overload indicator

- Fault Indicator in control panel
- Emergency push button with in-built LOTO [Lock out tag out]
- Floor indicator on control panel
- Enclosure with perforated sheet

NEW A NO.

ELECTRIC TOW TUGS - TT150 / TT250



15000 kg & 25000 kg towing capacity tugs for

- Heavy Engineering Industries
- Airports
- Defence
- Shipyards

TECHNICAL FEATURES

- Integrated digital display
- Inching facility at rear
- Auto distilled water filler unit

SAFETY FEATURES

- Dead man's pedal & seat sensor
- Emergency stop
- Dual charging port

ERGONOMIC FEATURES

- Integrated operator controls
- Tiltable steering wheel
- High visibility for operator

AIRPORT TROLLEY TUG - ATT5



Ideal for

- Terminal baggage trolley at airports
- Security runs in large campuses
- Pickups at large warehouses
- Light towing applications for industries

ERGONOMIC FEATURES

- Wide platform for operator
- Clear visibility
- Stable drive

Battery discharge indicator
FR

DISPLAY FEATURES

LED's for forward, neutral & reverse

SAFETY FEATURES

- Auto parking system
- Dead man pedal
- Emergency stop
- Low level battery warning
- Flash light
- Reverse buzzer



Powerful. Silent. Eco-Friendly.

Keep your carbon footprint in check with our range of eco-friendly products. Achieve this with exceptionall silent operations and enhanced performance



To know more about Maini's comprehensive solutions to simplify material handling, write to me at **mtrlsmov@maini.com**

MAINI BRANCH OFFICES

NORTH REGION : Gurgaon

SOUTH REGION : Bengaluru, Chennai

WEST REGION : Mumbai, Pune, Ahmedabad, Vadodara

PAN INDIA CHANNEL PARTNERS

- Ahmedabad Aurangabad Bengaluru Chandigarh Chennai
- Cochin Coimbatore Faridabad Ghaziabad Goa Gurqaon
- Guwahati Hyderabad Indore Kolhapur Kolkata Madurai
- Mumbai Nashik Pune Vapi Visakhapatnam

For enquiries please contact:

MAINI MATERIALS MOVEMENT PVT. LTD.

Sy. 32, Chandapura Hosur Road, Bengaluru - 560 099, INDIA. Phone: +91 80 4352 6555 • Fax: +91 80 4352 6580

Visit us at www.mainimaterials.com

Materials and specifications are subject to change without notice. All features are not necessarily a part of the standard equipment.